

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE UTAH-ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 219 TO MILE POST 226,

THE EAST, WEST AND NORTH BOUNDARIES,

AND

THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 1, 5, 6 AND 7,

IN

TOWNSHIP 43 SOUTH, RANGE 17 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

RONALD K. BAUGH
CADASTRAL SURVEYOR

Under special instructions dated and approved, **July 11, 2005**, which provided for the surveys included under Group Number **998**, and assignment instructions dated **July 11, 2005**.

Survey commenced **July 14, 2005**
Survey completed **September 18, 2005**

INDEX DIAGRAM

Township 43 South, Range 17 East

18	18	17	17	16	15	
14 6	47 5	38 4	33 3	28 2	23 1 10	
46	46	38	33	27	23	
14 7	44 8	37 9	32 10	27 11	22 12 9	
44	44	37	32	27	22	
13 18	43 17	36 16	31 15	26 14	21 13 8	
43	42	36	31	25	21	
12 19	42 20	35 21	30 22	25 23	21 24 8	
41	41	35	30	25	20	
12 30	40 29	34 28	29 27	25 26	20 25 7	
40	40	34	29	24	19	
11 31	39 32	33 33	28 34	24 35	19 36 7	
2	3	3	4	5	5	6
MP 219	MP 220	MP 221	MP 222	MP 223	MP 224	MP 225
UTAH - ARIZONA STATE BOUNDARY LINE						

The Subdivision of Section 1.....Page 47
The Subdivision of Section 5.....Page 49
The Subdivision of Section 6.....Page 51
The Subdivision of Section 7.....Page 53

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of the Utah - Arizona State Boundary Line, from Mile Post 219 to Mile Post 226, the East, West, North boundaries, and the subdivisional lines, and the subdivision of sections 1, 5, 6 and 7, in Township 43 South, Range 17 East, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by	Retr. or Resurveyed by
UTAH - ARIZONA STATE BOUNDARY LINE	
All H. B. Carpenter 1901	
All	W. W. Bandy 1924
EAST BOUNDARY	
All C. F. Moore & W. W. Bandy	1924
WEST BOUNDARY	
All C. F. Moore & W. W. Bandy	1924
NORTH BOUNDARY	
All C. F. Moore & W. W. Bandy	1924
SUBDIVISION	
All C. F. Moore & W. W. Bandy	1924

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 998, dated July 11, 2005.

The true meridian direction and length of all lines were determined by the Global Positioning System (GPS) utilizing Real-time kinematic (RTK) observations using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position, in NAD83 (CORS96), epoch 2002.00, for Mile Post 226 on the Utah - Arizona State Boundary Line, was determined by GPS observations to a network accuracy of less than 0.10 meters, 95 percent confidence circle, as defined in the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, May 9, 2001, Version 1.0, is as follows:

Latitude 36° 59' 54.309" N., Longitude 109° 58' 02.631" W.
N.A.D. 1983, N.A.V.D. 1988, Elevation: 4798.6 ft.

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

**DEPENDENT RESURVEY OF THE UTAH - ARIZONA STATE BOUNDARY LINE,
FROM MILE POST 219 TO MILE POST 226,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH**

Reestablishment of the Survey Executed by H. B. Carpenter in
1901 and the Dependent Resurvey by W. W. Bandy in 1924

Beginning at Mile Pipe 219, on the Utah - Arizona State
Boundary Line, monumented with an iron post, 3 inches in
diameter, firmly set and projecting 10 inches above ground,
firmly set against a large flat rock on its south side for
erosion protection, with brass cap marked as described in the
official record of the 1924 survey.

The marked stone was alongside the iron post, marked UTAH on
the north face and ARIZ dimly marked on south face.

Raise a mound of stone, 5x4 ft. base, 3 ft. high, south of the
corner.

Corner is located on a small finger ridge that bears north and
south, and on the east edge of a small wash that drains south.

N. 89° 59.5' E., along the 220th mile.

17.079 True point for the closing corner of T. 43 S., Rs. 16 and 17
E., sections 31 and 36, Not monumented.

From this true point, the 1924 closing corner bears S. 0°
02.9'W., 0.028 chains distance, monumented with an iron post,
3 inches diameter firmly set and projecting 6 inches above
ground with brass cap marked as described in the official
record of the 1924 survey. I added the marks AM 2005 to the
brass cap.

Set a steel fence post alongside the iron post.

Corner is located 26 links east of a 2 track road, bears
north and south.

56.713 Point for the 1/4 section corner of section 31 only, at
proportionate distance, there is no remaining evidence of the
original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches
diameter, 3 inches in the ground to bedrock, with a magnet at
base, and in a mound of stone 5 ft. base to top of brass cap
marked:

T 43 S R 17 E
1/4 S 31
2005

Raise a mound of stone, 5 ft base to top of brass cap.

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.044

Mile Post 220, monumented with an iron post, 3 inches in diameter, firmly set and projecting, 20 inches above a small mound of stone, with brass cap marked as described in the official record of the 1924 resurvey.

Rebuild the mound of stone 4 ft. base to top of the brass cap.

Corner is located on the east edge of a spur, bears north and south.

N. 89° 58.2' E., along the 221st mile.

16.663

Point for the closing corner of sections 31 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T 43 S	R 17 E
<u>S 31</u>	<u>S 32</u>
2005	

56.660

Point for the 1/4 section corner of section 32 only, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S	R 17 E
<u>1/4</u>	<u>S 32</u>
2005	

Set a steel fence post alongside the stainless steel post.

80.222

Mile Post 221, monumented with an iron post, 3 inches diameter, firmly set and projecting 10 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located on a semi steep west facing slope.

N. 89° 55.9' E., along the 222nd mile.

16.435

Point for the closing corner of sections 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with a brass cap marked:

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S	R 17 E
<u>S 32</u>	<u>S 33</u>
2005	

- 56.411** Point for the 1/4 section corner of section 33 only, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S	R 17 E
<u>1/4 S 33</u>	
2005	

Set a steel fence post alongside the stainless steel post.

- 79.987** Mile Post 222, monumented with an iron post, 3 inches diameter, firmly set and projection 3 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 55.9' E., along the 223rd mile.

- 16.400** Point for the closing corner of sections 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S	R 17 E
<u>S 33</u>	<u>S 34</u>
2005	

Set a steel fence post alongside the stainless steel post.

- 56.512** True point for the 1/4 section corner of section 34 only. Not monumented.

From this true point, the 1924 1/4 section corner bears South., 0.016 chains distance, monumented with an iron post, 3 inches diameter firmly set in a scattered mound of stone, with brass cap marked as described in the official record of the 1924 survey. I added the marks AM 2005 to the brass cap.

Set a steel fence post alongside the iron post.

Corner is located in rolling hills, in sage and grasses.

- 79.980** Mile Post 223, monumented with an iron post, 2 inches diameter, firmly set and projecting 12 inches above ground, with a cedar post alongside, with brass cap marked as described in the official record of the 1924 survey.

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in rolling hills in scattered sage and grasses.

N. 89° 56.5' E., along the 224th mile.

16.278 Point for the closing corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S	R 17 E
<u>S 34</u>	<u>S 35</u>
2005	

Set a steel fence post alongside the stainless steel post.

56.497 Point for the 1/4 section corner of section 35 only, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S	R 17 E
<u>1/4 S 35</u>	
2005	

Set a steel fence post alongside the stainless steel post.

80.042 Mile Post 224, monumented with an iron post, 2 inches diameter, firmly set and projecting 24 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

An iron post, 3 inches diameter, firmly set and projecting 14 inches above ground, alongside previous post, with brass cap marked:

UTAH
<u>224 M</u>
ARIZ
1924

This monument was not used in the course of this survey.

Corners are located in rolling hills in scattered brush.

N. 89° 57.9' E., along the 225th mile.

16.674 True point for the closing corner of sections 35 and 36. Not monumented.

TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From this true point, the 1924 closing corner bears N. $0^{\circ} 01.2'E.$, 0.006 chains distance, monumented with an iron post, 2 inches diameter firmly set and projecting 16 inches above ground with a mound of stone, 3 ft. base, 2 ft. high to the west, with brass cap marked as described in the official record of the 1924 survey. I added the marks AM 2005 to the brass cap.

56.866

True point for the $1/4$ section corner of section 36 only. Not monumented.

From this true point, the 1924 $1/4$ section corner bears North, 0.006 chains distance, monumented with an iron post, 1 inch diameter, firmly set and projecting 14 inches above a scattered mound of stone, with brass cap marked as described in the official record of the 1924 survey. I added the marks AM 2005 to the brass cap.

Set a steel fence post alongside the iron post.

Corner is located on the west edge of a wash that drains NNE.

79.792

Mile Post 225, monumented with an iron post, 2 inches diameter, firmly set and projecting 16 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Corner is located 14 ft. south, of a cedar post, and 8 ft. south of a wash that drains northwesterly.

N. $89^{\circ} 54.1'E.$, along the 226th mile.

17.119

True point for the closing corner of T. 43 S., Rs. 17 and 18 E., sections 31 and 36, on the east boundary of the township.

From this true point, the 1924 closing corner bears S. $0^{\circ} 00.1'E.$, 0.011 chains distance, monumented with an iron post, 3 inches diameter firmly set and projecting 2 inches above ground with brass cap marked as described in the official record of the 1924 survey. Add marks AM 2005 to the brass cap.

Set a steel fence post alongside the iron post.

Corner is located at base of easterly hillside in scattered brush.

80.318

Mile post 226, monumented with a iron post, 3 inches diameter, firmly set projecting 6 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1924 survey.

Corner is located in rolling hills in scattered sage and grasses.

CHAINS

**DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH**

Reestablishment of the Survey Executed by C. F. Moore and
W. W. Bandy in 1924

From the true point for the closing corner of T. 43 S., Rs. 17 and 18 E. sections 31 and 36, on the east boundary of the township, hereinbefore described.

N. 0° 00.1' W., between sections 31 and 36.

37.866

The 1/4 section corner of sections 31 and 36, monumented with an iron post, 1 inch diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located on a south slope, 15 links distance north of a wash, drains westerly.

N. 0° 02.7' E., beginning new measurement.

39.982

The corner of sections 25, 30, 31 and 36, monumented with a sandstone, 3x6x6 inches, 3 inches marked with an "X" chiseled on top, 26 inches below the ground, as stated in the 1924 record.

From this point, the 1924 iron post was found about 500 ft. south, lying on top of the ground.

At the corner point (sandstone with cross)

Reset the 1924 iron post, and a magnet, 26 inches in the ground over the cross on top of stone, with brass cap marked as described in the official record of the 1924 survey.

Deposit the sandstone alongside the iron post.

Set a steel fence post alongside the iron post.

Corner is located in rolling hills in scattered sage and grasses.

N. 0° 01.9' E., between sections 25 and 30.

39.998

The 1/4 section corner of sections 25 and 30, monumented with an iron post, 1 inch diameter, projecting 12 inches above

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

ground, with brass cap marked as described in official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located in rolling hills in scattered sage and grasses.

N. 0° 01.4' E., beginning new measurement.

39.991 The corner of sections 19, 24, 25 and 30, monumented with an iron post, 2 inches diameter, projecting 6 inches above ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located in rolling hills in scattered brush.

N. 0° 00.4' W., between sections 19 and 24.

39.959 The 1/4 section corner of sections 19 and 24, monumented with an iron post, 1 inch diameter, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 0° 00.2' E., beginning new measurement.

40.007 The corner of sections 13, 18, 19 and 24, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainlesssteel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S	
R 17 E	R 18 E
S 13	S 18
S 24	S 19
2005	

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 01.3' E., between sections 13 and 18.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

39.997

The 1/4 section corner of sections 13 and 18, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 42 S
R 17 E R 18 E
1/4
S 13 | S 18
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 03.2' W., beginning new measurement.

40.001

The corner of sections 7, 12, 13 and 18, monumented with a small mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S
R 17 E R 18 E
S 12 | S 7
S 13 | S 18
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 04.0' E., between sections 7 and 12.

39.976

The 1/4 section corner of sections 7 and 12, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the stainless steel post.

N. 0° 00.1' W., beginning new measurement.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS
39.987

The corner of sections 1, 6, 7 and 12, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S	
R 17 E	R 18 E
S 1	S 6
S 12	S 7
2005	

Set a steel fence post alongside the stainless steel post.

Corner is located approximately 1.50 chains distance north of a house.

N. 0° 00.8' E., between sections 1 and 6.

8.050 Intersect the centerline of a gravel road with approximately a 70 ft. right-of-way, bears S. 53° E. and N. 53° W.

19.976 Point for the S 1/16 section corner of sections 1 and 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S	
R 17 E	R 18 E
S 1/16	
S 1	S 6
2005	

Set a steel fence post alongside the stainless steel post.

39.952 The 1/4 section corner of sections 1 and 6, monumented with an iron post, 1 inch diameter, firmly set and projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 00.6' E., beginning new measurement.

19.987 Point for the N 1/16 section corner of sections 1 and 6.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked.

T 43 S
R 17 E R 18 E
N 1/16
S 1 | S 6
2005

Set a steel fence post alongside the stainless steel post.

39.974

The corner of sections 1, 6, 31 and 36, Tps. 42 and 43 S., Rs. 17 and 18 E., monumented with an iron post, 3 inches diameter, firmly set and projecting 4 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the stainless steel post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

Reestablishment of the Survey Executed by C. F. Moore and W. W. Bandy in 1924

From the true point for the closing corner of T. 43 S., Rs. 16 and 17 W., sections 31 and 36, on the west boundary of the township hereinbefore described.

N. 0° 02.9' E., between sections 31 and 36.

38.602

The 1/4 section corner of sections 31 and 36, monumented with a small mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S
R 16 E R 17 E
1/4
S 36 | S 31
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 00.3' W., beginning new measurement.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS
39.988

The corner of sections 25, 30, 31 and 36, monumented with an iron post, 2 inches diameter, loosely set in a small mound of stone.

At the corner point

Reset the iron post, 20 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

N. 0° 05.6' E., between sections 25 and 30.

40.012

The 1/4 section corner of sections 25 and 30, monumented with an iron post, 1 inch diameter, loosely set in a small mound of stone.

At the corner point

Reset the iron post, 8 inches in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

N. 0° 05.5' E., beginning new measurement.

40.012

The corner of sections 19, 24, 25 and 30, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 6 ft. base to top of brass cap marked:

T 43 S	
R 17 E	R 18 E
S 24	S 19
S 25	S 30
2005	

N. 0° 01.3' E., between sections 19 and 24.

40.047

The 1/4 section corner of sections 19 and 24, monumented with an iron post, 1 inch diameter, firmly set and projecting 18 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Raise a mound of stone, 3 ft. base to the top of the brass cap.

From which

A cedar, marked 1/4 S 24 BT on an open blaze, bears S. 57° 00' E., 134 links distance.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 04.9' E., beginning new measurement.

- 40.032** Point for the corner of sections 13, 18, 19 and 24, at proportionate distance. The 1924 iron post was found lying loose nearby.

Reset the iron post, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

Added the marks 2005 to the monument.

Corner is located in a small draw, drains north.

N. 0° 04.9' E., between sections 13 and 18.

- 40.032** Point for the 1/4 section corner of sections 13 and 18, at proportionate distance. The 1924 iron post was found lying loose nearby.

Reset the iron post, 18 inches in the ground to bedrock, in a mound of stone, 2 ft. base to top of brass cap marked as described in the official record of the 1924 survey. Add marks 2005 to the monument.

From this corner, a right-of-way marker on the southeast side of United States Highway No. 163, a paved road, bears N. 34° 54.6' W., 9.337 chains distance.

From this same corner, a right-of-way marker on the northwest side of United States Highway No. 163, a paved road, bears N. 36° 11.5' W., 11.598 chains distance.

- 54.839** The centerline of United States Highway No. 163, a paved road, with a 150 feet between rights-of-way, bears N. 34° 26.1' E. and S. 34° 26.1' W.

- 80.064** The corner of sections 7, 12, 13 and 18, monumented with an iron post, 1 1/2 inches diameter, projecting 14 inches above ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1924 survey.

Corner is located on a flat mesa in scattered sage and brush.

From which

A cedar, 10 inches diameter, with an open blaze and no visible marks, bears S. 0° 23.5' E., 1.456 chains distance.

A cedar, 8 inches diameter, with an open blaze and no visible marks, bears N. 64° 52.2' W., 1.555 chains distance.

There are no other BTs. within the area.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 03.0' E., between sections 7 and 12.

40.016 Point for the 1/4 section corner of sections 7 and 12 at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

	T 43 S	
R 16 E		R 17 E
	1/4	
S 12		S 7
	2005	

Set a steel fence post alongside the stainless steel post.

80.032 Point for the corner of sections 1, 6, 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

	T 43 S	
R 16 E		R 17 E
S 1		S 6
S 12		S 7
	2005	

Set a steel fence post alongside the stainless steel post.

N. 0° 03.0' E., between sections 1 and 6.

40.016 Point for the 1/4 section corner of sections 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with a magnet at base, with brass cap marked:

	T 43 S	
R 16 E		R 17 E
	1/4	
S 1		S 6
	2005	

Set a steel fence post alongside the stainless steel post.

60.024 Point for the N 1/16 section corner of sections 1 and 6.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T 43 S
N 1/16
S 1 | S 6
16 E R 17 E
2005

Set a steel fence post alongside the stainless steel post.

80.032

The corner of Ts. 42 and 43 S., Rs. 16 and 17 E., sections 1, 6, 31 and 36, monumented with an iron post, 3 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

From which

A cedar, 10 inches in diameter, with an open blaze and no visible marks, bears S. 10° 32.9' E., 2.894 chains distance.

A cedar, 10 inches in diameter, with an open blaze and no visible marks, bears N. 7° 04.0' W., 3.617 chains distance.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

Reestablishment of the Survey Executed by C. F. Moore and W. W. Bandy in 1924

From the corner of Ts. 42 and 43 S., Rs. 17 and 18 E., sections 1, 6, 31 and 36, hereinbefore described.

N. 89° 53.1' W., between sections 1 and 36.

39.964

The 1/4 section corner of sections 1 and 36, monumented with an iron post, 1 inch diameter, firmly set and projecting 11 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 59.1' W., beginning new measurement.

40.033

The corner of sections 1, 2, 35 and 36, monumented with an iron post, 2 inches diameter, set in a small mound of stone, with no brass cap.

At the corner point

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T 42 S R 17 E	
S 35	S 36
S 2	S 1
T 43 S	
2005	

Deposit the 2 inch iron post alongside the stainless steel post.

N. 89° 56.2' W., between sections 2 and 35.

17.157 The centerline of a gravel road approximately a 70 ft. wide, bears S. 56° E. and N. 56° W.

39.954 Point for the 1/4 section corner of sections 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 42 S R 17 E	
S 35	
1/4	_____
S 2	
T 43 S	
2005	

Set a steel fence post alongside the stainless steel post.

69.319 The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. 50° 08.6' E. and S. 50° 08.6' W.

79.908 The corner of sections 2, 3, 34 and 35, monumented with sandstone, 4x4x2 inches, with a cross "X" on top and in a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground over the top of the sandstone, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T 42 S R 17 E	
S 34	S 35
S 3	S 2
T 43 S	
2005	

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From this corner, a right-of-way marker on the southeast side of United States Highway No. 163, bears N. 85° 44.8' E., 13.630 chains distance.

From this same corner, a right-of-way marker on the northwest side of United States Highway No. 163, bears N. 77° 12.2' E., 12.441 chains distance.

N. 89° 54.9' W., between sections 3 and 34.

39.990 Point for the 1/4 section corner of sections 3 and 34, at proportionate distance. The 1924 iron post was found lying loose nearby.

Reset the iron post, 15 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1924 survey. Add marks 2005 to the iron post.

79.980 The corner of sections 3, 4, 33 and 34, monumented with an iron post, 2 inches diameter, firmly set and projecting 13 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 89° 54.4' W., between sections 4 and 33.

39.964 The 1/4 section corner of sections 4 and 33, monumented with an iron post, 2 inches diameter, firmly set and projecting 15 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Corner is located east, 1.10 chains distance from a draw that drains NNE.

N. 89° 55.5' W., beginning new measurement.

39.955 The corner of sections 4, 5, 32 and 33, monumented with an iron post, 2 inches diameter, firmly set and projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 58.5' W., between sections 5 and 32.

19.991

Point for the E 1/16 section corner of sections 5 and 32.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

	T 42 S R 17 E
	S 32
E 1/16	_____
	S 5
	T 43 S
	2005

Set a steel fence post alongside the stainless steel post.

39.982

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

	T 42 S R 17 E
	S 32
1/4	_____
	S 5
	T 43 S
	2005

Set a steel fence post alongside the stainless steel post.

79.964

The corner of sections 5, 6, 31 and 32, monumented with an iron post, 2 inches diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 47.0' W., between sections 6 and 31.

39.836

The 1/4 section corner of sections 6 and 31, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, with a magnet at base, in the mound of stone, 5 ft. base to top of brass cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 42 S R 17 E
S 31
1/4 —————
S 6
2005

N. 89° 49.8' W., beginning new measurement.

39.578

The corner of, Ts. 42 and 43 S., Rs. 16 and 17 E., sections 1, 6, 31 and 36, hereinbefore described.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

Reestablishment of the Survey Executed by C. F. Moore and W.
W. Bandy in 1924

From the true point for the closing corner of sections 35 and 36, on the Utah - Arizona State Boundary Line, hereinbefore described.

N. 0° 01.2' E., between sections 35 and 36.

37.829

The 1/4 section corner of sections 35 and 36, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 0° 00.2' E., beginning new measurement.

40.017

Point for the corner of sections 25, 26, 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S R 17 E
S 26 | S 25
S 35 | S 36
2005

Set a steel fence post alongside the stainless steel post.

From the corner of sections 25, 30, 31 and 36, on the east boundary of the township, hereinbefore described.

S. 89° 57.0' W., between sections 25 and 36.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.117

Point for the 1/4 section corner of sections 25 and 36, at proportionate distance. The 1924 iron post was found lying loose nearby.

Reset the iron post, 29 inches in the ground, with brass cap marked as described in the official record of the 1924 survey.

Add marks 2005 to the brass cap.

Set a steel fence post alongside the iron post.

80.234

The corner of sections 25, 26, 35 and 36.

N. 0° 00.3' E., between sections 25 and 26.

40.017

Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 26 | S25
2005

Set a steel fence post alongside the stainless steel post.

80.034

The corner of sections 23, 24, 25 and 26, monumented with a small mound of stone. The 1924 iron post was found lying loose nearby.

At the corner point (center of the mound)

Reset the iron post, 6 inches in the ground to bedrock, in mound of stone, 5 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

From the corner of sections 19, 24, 25 and 30, on the east boundary of the township, hereinbefore described.

S. 89° 57.3' W., between sections 24 and 25.

40.204

The 1/4 section corner of sections 24 and 25, monumented with an iron post, 1 inch diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 59.3' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS
40.460

The corner of sections 23, 24, 25 and 26.

N. $0^{\circ} 04.6'$ E., between sections 23 and 24.

40.013

Point for the $1/4$ section corner of sections 23 and 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 24 inches in the ground, with brass cap marked:

T 43 S R 17 E
1/4
S 23 | S 24
2005

Set a steel fence post alongside the stainless steel post.

Corner is located 50 links south of a trail road, bears SSE and NNW.

80.026

The corner of sections 13, 14, 23 and 24, monumented with an iron post, 2 inches diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

From the corner of sections 13, 18, 19 and 24, on the east boundary of the township, hereinbefore described.

N. $89^{\circ} 59.6'$ W., between sections 13 and 24.

40.073

The $1/4$ section corner of sections 13 and 24, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. $89^{\circ} 57.3'$ W., beginning new measurement.

40.053

The corner of sections 13, 14, 23 and 24.

N. $0^{\circ} 02.2'$ E., between sections 13 and 14.

39.998

The $1/4$ section corner of sections 13 and 14, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 00.7' E., beginning new measurement.

39.989

The corner of sections 11, 12, 13 and 14, monumented with an iron post, 2 inches diameter; projecting 14 inches above ground, in a collar of stone, with a mound of stone, 3 ft. base, 3 ft. high, west of corner, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located on a westerly slope, 30 links east of a wash, drains southerly.

From the corner of sections 7, 12, 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89° 58.8' W., between sections 12 and 13.

40.017

The 1/4 section corner of sections 12 and 13, monumented with an iron post, 1 inch diameter, projecting 5 inches above ground, with a small mound of stone to the north, with brass cap marked as described in the official record of the 1924 survey.

N. 89° 59.1' W., beginning new measurement.

40.038

The corner of sections 11, 12, 13 and 14.

N. 0° 03.4' E., between sections 11 and 12.

39.986

The 1/4 section corner of sections 11 and 12, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E

1/4

S 11 | S 12

2005

N. 0° 02.7' E., beginning new measurement.

39.989

The corner of sections 1, 2, 11 and 12, monumented with an iron post, 2 inches diameter, projecting 12 inches above ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1924 survey.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the iron post.

Corner is located in rolling hills in scattered brush.

From the corner of sections 1, 6, 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89° 58.4' W., between sections 1 and 12.

40.008

Point for the 1/4 section corner of sections 1 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
S 1
1/4 ———
S 12
2005

Set a steel fence post alongside the stainless steel post.

80.016

The corner of sections 1, 2, 11 and 12.

N. 0° 01.4' E., between sections 1 and 2.

40.001

The 1/4 section corner of sections 1 and 2, monumented with a sandstone, 8x5x3 inches, with a cross "X" on top, there is no remaining evidence of the 1924 iron post.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground over the top of the sandstone, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 2 | S 1
2005

Set a steel fence post alongside the stainless steel post.

N. 0° 00.3' E., beginning new measurement.

28.501

The centerline of a gravel road approximately 70 ft. wide, bears S. 56° E. and N. 56° W.

39.980

The corner of sections 1, 2, 35 and 36, on the north boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the closing corner of sections 34 and 35, on the Utah-Arizona State Boundary Line, hereinbefore described.

N. $0^{\circ} 01.1'$ E., between sections 34 and 35.

38.050

The $1/4$ section corner of sections 34 and 35, monumented with a small mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 26 inches in the ground, with the brass cap marked:

T 43 S R 17 E
1/4
S 34 | S 35
2005

Raise a mound of stone, 2 ft. base, 2 ft. high, west of the stainless steel post.

N. $0^{\circ} 07.7'$ E., beginning new measurement.

39.985

The corner of sections 26, 27, 34 and 35, monumented with an iron post, 2 inches diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

From the corner of sections 25, 26, 35 and 36.

N. $89^{\circ} 55.1'$ W., between sections 26 and 35.

40.167

Point for the $1/4$ section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
S 26
1/4 ———
S 35
2005

Set a steel fence post alongside the stainless steel post.

80.334

The corner of sections 26, 27, 34 and 35.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 04.2'$ E., between sections 26 and 27.

40.004

Point for the $1/4$ section corner of sections 26 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 27 | S 26
2005

Set a steel fence post alongside the stainless steel post.

80.008

The corner of sections 22, 23, 26 and 27, monumented with an iron post, 2 inches diameter, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

From the corner of sections 23, 24, 25 and 26.

N. $89^{\circ} 56.3'$ W., between sections 23 and 26.

40.114

Point for the $1/4$ section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
S 23
1/4 ———
S 26
2005

Set a steel fence post alongside the stainless steel post.

80.228

The corner of sections 22, 23, 26 and 27,

N. $0^{\circ} 04.7'$ E., between sections 22 and 23.

40.010

The $1/4$ section corner of sections 22 and 23, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 05.7'$ E., beginning new measurement.

40.022

The corner of sections 14, 15, 22 and 23, monumented with an iron post, 2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located, 1.90 chains south of a dirt road, that bears east and west, and falls in a flat scattered brush terrain.

From the corner of sections 13, 14, 23 and 24.

N. $89^{\circ} 56.3'$ W., between sections 14 and 23.

40.136

The 1/4 section corner of sections 14 and 23, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located in flat scattered brush terrain.

N. $89^{\circ} 55.9'$ W., beginning new measurement.

40.064

The corner of sections 14, 15, 22 and 23.

N. $0^{\circ} 05.2'$ E., between sections 14 and 15.

39.985

The 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with a small mound of stone to the west, with brass cap marked as described in the official record of the 1924 survey.

Rebuild the mound of stone, 3 ft. base, 2 ft. high, west of the iron post.

N. $0^{\circ} 07.3'$ E., beginning new measurement.

40.024

The corner of sections 10, 11, 14 and 15, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S	R 17 E
S 10	S 11
S 15	S 14
2005	

Corner is located on a northerly facing slope.

From the corner of sections 11, 12, 13 and 14.

N. 89° 55.6' W., between sections 11 and 14.

- 40.010** The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 54.7' W., beginning new measurement.

- 40.062** The corner of sections 10, 11, 14 and 15.
-

N. 0° 03.6' E., between sections 10 and 11.

- 39.967** The 1/4 section corner of sections 10 and 11, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, in a mound of stone, 2 ft. base to top of brass cap marked as described in the official record of the 1924 survey.
-

N. 0° 05.1' E., beginning new measurement.

- 40.007** The corner of sections 2, 3, 10 and 11, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, in a collar of stone, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

From the corner of sections 1, 2, 11 and 12.

N. 89° 54.0' W., between sections 2 and 11.

- 40.016** The 1/4 section corner of sections 2 and 11, monumented with an iron post, 1 inch diameter, projecting 2 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a Steel fence post alongside the iron post.

N. 89° 56.3' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.011

The corner of sections 2, 3, 10 and 11.

N. $0^{\circ} 06.6'$ E., between sections 2 and 3.

40.009

The $1/4$ section corner of sections 2 and 3, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Raise a mound of stone, 2 ft. high, 2 ft. diameter, west of the iron post.

N. $0^{\circ} 04.0'$ E., beginning new measurement.

31.088

The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. $50^{\circ} 08.6'$ E. and S. $50^{\circ} 08.6'$ W.

39.949

The corner of sections 2, 3, 34 and 35, of the north boundary of the township, hereinbefore described.

From the closing corner of sections 33 and 34, on the south boundary of the township, hereinbefore described.

N. $0^{\circ} 05.3'$ W., between sections 33 and 34.

38.283

The $1/4$ section corner of sections 33 and 34, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. $0^{\circ} 02.1'$ W., beginning new measurement.

40.018

The corner of sections 27, 28, 33 and 34, monumented with a sandstone, 11x9x3 inches, 6 inches below ground, with a cross "X" on top, there is no remaining evidence of the 1924 iron post

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S	R 17 E
S 28	S 27
S 33	S 34
2005	

Deposit the marked stone alongside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

From the corner of sections 26, 27, 34 and 35.

N. 89° 52.0' W., between sections 27 and 34.

40.029

The 1/4 section corner of sections 27 and 34, monumented with a sandstone, 6x4x4 inches, on top of the ground, with a cross "X" on top, there is no remaining evidence of the 1924 iron post.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S	R 17 E
S 27	
1/4	
S 34	
2005	

Deposit the marked stone alongside the stainless steel post.

Set a steel fence post alongside the stainless steel post.

N. 89° 53.0' W., beginning new measurement.

39.999

The corner of sections 27, 28, 33 and 34.

N. 0° 02.0' W., between sections 27 and 28.

39.979

Point for the 1/4 section corner of sections 27 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a brass cap marked:

T 43 S	R 17 E
1/4	
S 28	S 27
2005	

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the stainless steel post.

- 79.958 The corner of sections 21, 22, 27 and 28, monumented with an iron post, 2 inches diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located in rolling in scattered brush.

From the corner of sections 22, 23, 26 and 27.

N. 89° 51.2' W., between sections 22 and 27.

- 40.190 The 1/4 section corner of sections 22 and 27, monumented with an iron post, 2 inches diameter, projecting 20 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 58.3' W., beginning new measurement.

- 39.966 The corner of sections 21, 22, 27 and 28.

N. 0° 05.8' E., between sections 21 and 22.

- 39.990 The 1/4 section corner of sections 21 and 22, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 0° 17.8' E., beginning new measurement.

- 40.047 Point for the corner of sections 15, 16, 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E	
S 16	S 15
S 21	S 22
2005	

Set a steel fence post alongside the stainless steel post.

From the corner of sections 14, 15, 22 and 23.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 48.6' W., between sections 15 and 22.

39.966 The 1/4 section corner of sections 15 and 22, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

S. 89° 59.7' W., beginning new measurement.

40.022 The corner of sections 15, 16, 21 and 22.

N. 0° 08.7' W., between sections 15 and 16.

40.047 The 1/4 section corner of sections 15 and 16, is determined from record bearing and distance from the remains of the original bearing trees.

A burnt off stump of a cedar, bears S. 53° E., 1.65 chains distance.

A cedar, 12 inches diameter, bears N. 68° W., 2.35 chains distance. It was incorrectly marked: 1/4 S 15 BT.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 16 | S 15
2005

Set a steel fence post alongside the stainless steel post.

N. 0° 07.1' E., beginning new measurement.

39.944 The corner of sections 9, 10, 15 and 16, monumented with an iron post, 1 inch diameter, projecting 30 inches above ground and tilted on a 45° angle, with a brass cap marked as described in the official record of the 1924 survey.

At the corner point

Reset the iron post, in a mound of stone, 5 ft. base to top of brass cap.

Corner is located on a steep westerly facing slope, halfway up a hill.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 10, 11, 14 and 15.

N. $89^{\circ} 53.8'$ W., between sections 10 and 15.

- 40.107** The 1/4 section corner of sections 10 and 15, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground. with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. $89^{\circ} 56.7'$ W., beginning new measurement.

- 40.030** The corner of sections 9, 10, 15 and 16.
-

N. $0^{\circ} 10.7'$ E., between sections 9 and 10.

- 39.948** The 1/4 section corner of sections 9 and 10, monumented with an iron post, 1 inch diameter, loosely set, tilted on a 45° angle to the east, with brass cap marked as described in the official record of the 1924 survey.

At the corner point

Reset the iron post in place, in a mound of stone, 5 ft. base to top of brass cap.

Corner is located between two drainages which drain east.

N. $0^{\circ} 05.7'$ E., beginning new measurement.

- 33.195** The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. $49^{\circ} 25.4'$ E. and S. $49^{\circ} 25.4'$ W.

- 39.953** The corner of sections 3, 4, 9 and 10, monumented with a broken sandstone, 5x4x2 inches, lying loose on top of the ground, with a cross "X" on top, there is no remaining evidence of the 1924 iron post.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marker:

T 43 S		R 17 E	
S 4		S 3	
S 9		S 10	
2005			

Deposit the marked stone alongside the stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the stainless steel post.

From the corner of sections 2, 3, 10 and 11.

N. 89° 57.1' W., between sections 3 and 10.

- 39.933** The 1/4 section corner of sections 3 and 10, monumented with an iron post, 1 inch diameter, projecting 4 inches above a mound of stone, 3 ft. base, 2 ft. high, with brass cap marked as described in the official record of the 1924 survey.
-

N. 89° 59.8' W., beginning new measurement.

- 32.222** The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. 49° 25.4' E. and S. 49° 25.4' W.

- 40.100** The corner of sections 3, 4, 9 and 10.
-

N. 0° 06.9' E., between sections 3 and 4.

- 40.020** Point for the 1/4 section corner of sections 3 and 4, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 4 | S 3
2005

Set a steel fence post alongside the stainless steel post.

- 80.040** The corner of sections 3, 4, 33 and 34, on the north boundary of the township, hereinbefore described.
-

From the closing corner of sections 32 and 33, on the Utah-Arizona State Boundary Line, hereinbefore described.

N. 0° 01.0' E., between sections 32 and 33.

- 38.504** Point for the 1/4 section corner of sections 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 32 | S 33
2005

78.498 Point for the corner of sections 28, 29, 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground with a magnet at base, with brass cap marked:

T 43 S R 17 E
S 29 | S 28
S 32 | S 33
2005

Set a steel fence post alongside the stainless steel post.

From the corner of sections 27, 28, 33 and 34.

N. 89° 55.7' W., between sections 28 and 33.

39.916 Point for the 1/4 section corner of sections 28 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S R 17 E
S 28
1/4
S 33
2005

Set a steel fence post alongside the stainless steel post.

79.832 The corner of sections 28, 29, 32 and 33.

N. 0° 06.4' E., between sections 28 and 29.

39.994 The 1/4 section corner of sections 28 and 29, monumented with an iron post, 1 inch diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 05.5'$ E., beginning new measurement.

39.995

The corner of sections 20, 21, 28 and 29, monumented with an iron post, 2 inches diameter, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

Corner is located in rolling hills in scattered brush.

From the corner of sections 21, 22, 27 and 28.

N. $89^{\circ} 51.9'$ W., between sections 21 and 28.

39.793

The $1/4$ section corner of sections 21 and 28, monumented with a small mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 18 inches in the ground to bedrock, in mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E
S 21
 $1/4$ —————
S 28
2005

Corner is located 2.000 chains north of a wash, drains east.

N. $89^{\circ} 57.0'$ W., beginning new measurement.

39.839

The corner of sections 20, 21, 28 and 29.

N. $0^{\circ} 03.6'$ E., between sections 20 and 21.

40.058

Point for the $1/4$ section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 20 | S 21
2005

Set a steel fence post alongside the stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.116

The corner of sections 16, 17, 20 and 21, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in the mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E	
S 17	S 16
S 20	S 21
2005	

From the corner of sections 15, 16, 21 and 22.

N. 89° 56.3' W., between sections 16 and 21.

39.892

The 1/4 section corner of sections 16 and 21, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 89° 45.8' W., beginning new measurement.

39.915

The corner of sections 16, 17, 20 and 21.

N. 0° 00.6' E., between sections 16 and 17.

40.001

The 1/4 section corner of sections 16 and 17, monumented with an iron post, 1 inch diameter, projecting 14 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 0° 05.5' E., beginning new measurement.

39.958

Point for the corner of sections 8, 9, 16 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E	
S 8	S 9
S 17	S 16
2005	

Set a steel fence post alongside the stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 9, 10, 15 and 16.

N. $89^{\circ} 52.4'$ W., between sections 9 and 16.

39.850 Point for the 1/4 section corner of sections 9 and 16, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
S 9
1/4 —————
S 16
2005

Set a steel fence post alongside the stainless steel post.

79.700 The corner of sections 8, 9, 16 and 17.

N. $0^{\circ} 09.2'$ W., between sections 8 and 9.

39.958 The 1/4 section corner of sections 8 and 9, monumented with a mound of stone, there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, with a magnet at base, in the mound of stone, 3 ft. base to top of brass cap marked:

T 43 S R 17 E
1/4
S 8 | S 9
2005

N. $0^{\circ} 05.8'$ E., beginning new measurement.

24.898 The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears S. $88^{\circ} 15'$ E. and N. $88^{\circ} 15'$ W.

39.990 The corner of sections 4, 5, 8 and 9, monumented with an iron post, 2 inches diameter, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on a westerly slope about 75 links north of a rock ledge.

From the corner of sections 3, 4, 9 and 10.

N. $89^{\circ} 50.3'$ W., between sections 4 and 9.

39.834

The $1/4$ section corner of sections 4 and 9, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 8 inches in the ground to bedrock, with a magnet at base, in the mound of stone, 4 ft. base to top of brass cap marked:

T 43 S R 17 E
S 4
 $\frac{1}{4}$ —————
S 9
2005

N. $89^{\circ} 50.5'$ W., beginning new measurement.

40.083

The corner of sections 4, 5, 8 and 9.

N. $0^{\circ} 06.1'$ E., between sections 4 and 5.

19.984

Point for the $S\frac{1}{16}$ section corner of sections 4 and 5.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
S $\frac{1}{16}$
S 5 | S 4
2005

Set a steel fence post alongside the stainless steel post.

39.968

Point for the $1/4$ section corner of sections 4 and 5, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, $2\frac{1}{2}$ inches diameter, 20 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 17 E
1/4
S 5 | S 4
2005

Set a steel fence post alongside the stainless steel post.

59.952 Point for the N 1/16 section corner of sections 4 and 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on solid rock, in a mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E
N 1/16
S 5 | S 4
2005

79.936 The corner of sections 4, 5, 32 and 33, on the north boundary of the township, hereinbefore described.

From the closing corner of sections 31 and 32, on the Utah-Arizona State Boundary Line, hereinbefore described.

N. 0° 07.0' E., between sections 31 and 32.

38.460 Point for the 1/4 section corner of sections 31 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 31 | S 32
2005

Set a steel fence post alongside the stainless steel post.

78.544 Point for the corner of sections 29, 30, 31 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S R 17 E
S 30 | S 29
S 31 | S 32
2005

Set a steel fence post alongside the stainless steel post.

Corner is located in the bottom of a small draw, drains SSW.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 28, 29, 32 and 33.

S. 89° 59.7' W., between sections 29 and 32.

39.920 Point for the 1/4 section corner of sections 29 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T 43 S R 17 E
S 29
1/4 —————
S 32
2005

Set a steel fence post alongside the stainless steel post.

79.840 The corner of sections 29, 30, 31 and 32.

N. 89° 58.8' W., between sections 30 and 31.

40.016 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Point falls on a hill side too steep for a monument.

40.087 Point selected for the witness 1/4 section corner of sections 30 and 31, in the bottom of a swale, drains ESE.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 2 inches in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap marked:

W C
T 43 S R 17 E
S 30
1/4 —————→
S 31
2005

Set a steel fence post alongside the stainless steel post.

79.742 The corner of sections 25, 30, 31 and 36, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31 and 32.

N. 0° 04.6' E., between sections 29 and 30.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.084

Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 30 | S 29
2005

Set a steel fence post alongside the stainless steel post.

80.168

The corner of sections 19, 20, 29 and 30, monumented with an iron post, 2 inches diameter, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the stainless steel post.

From the corner of sections 20, 21, 28 and 29.

S. 89° 59.4' W., between sections 20 and 29.

40.313

The 1/4 section corner of sections 20 and 29, monumented with an iron post 1 inch diameter, loosely set in a mound of stone.

At the corner point

Reset the iron post, 18 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

Set a steel fence post alongside the iron post.

N. 89° 44.2' W., beginning new measurement.

39.545

The corner of sections 19, 20, 29 and 30.

S 89° 52.7' W., between sections 19 and 30.

39.968

The 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 inch diameter, loosely set in a small mound of stone.

At the corner point

Reset the iron post, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1924 survey.

Corner is located of a steep WNW slope.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 57.2' W., beginning new measurement.

- 39.738** The corner of sections 19, 24, 25 and 30, on the west boundary of the township, hereinbefore described.
-

From the corner of sections 19, 20, 29 and 30.

N. 0° 05.9' E., between sections 19 and 20.

- 39.910** The 1/4 section corner of sections 19 and 20, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in the mound of stone, 3 ft. base to top of brass cap marked:

T 43 S R 17 E
1/4
S 19 | S 20
2005

N. 0° 02.2' E., beginning new measurement.

- 40.034** The corner of sections 17, 18, 19 and 20, monumented with an iron post, 2 inches diameter, in a small mound of stone, with brass cap marked as described in the official record of the 1924 survey.

Rebuild the mound of stone, 5 ft. base to top of brass cap.

Corner is located 80 links south, of a ledge that bears east and west, and in the bottom of a draw, drains NNE.

From the corner of sections 16, 17, 20 and 21.

West, between sections 17 and 20.

- 39.917** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, There is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 17 E
S 17
1/4 ———
S 20
2005

- 79.834** The corner of sections 17, 18, 19 and 20.
-
- N. 89° 56.4' W., between sections 18 and 19.
- 40.215** The 1/4 section corner of sections 18 and 19, monumented with an iron post, 1 inch diameter, loosely set in a small mound of stone, with brass cap marked as described in the official record of the 1924 survey.
- Rebuild the mound of stone, 4 ft. base to top of brass cap.
- Corner is located on a steep south slope.
-
- S. 89° 58.1' W., beginning new measurement,
- 39.497** The corner of sections 13, 18, 19 and 24, on the west boundary of the township, hereinbefore described.
-
- From the corner of sections 17, 18, 19 and 20.
- N. 0° 08.6' W., between sections 17 and 18.
- 39.753** The 1/4 section corner of sections 17 and 18, monumented with an iron post, 1 inch diameter, projecting 24 inches above ground in a small mound of stone, with brass cap marked as described in the official record of the 1924 survey.
- Rebuilt the mound of stone, 5 ft. base to top of brass cap.
-
- N. 0° 14.4' E., beginning new measurement.
- 40.117** The corner of sections 7, 8, 17 and 18, is determined at record bearing and distance from the remains of the original bearing trees.
- A cedar, 15 inches diameter, bears N. 54° 15' E., 237 links distance, no scribe marks visible.
- A cedar, in southeast quarter, no remaining evidence.
- A cedar, 12 inches diameter, bears S. 19° W., 109 links distance, marked: BT only on open blaze.
- A cedar, 12 inches diameter, bears N. 62° W., 92 links distance, marked: T 43 S R 17 E on a open blaze.
- At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E	
S 7	S 8
S 18	S 17
2005	

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the stainless steel post.

From the corner of sections 8, 9, 16 and 17.

S. 89° 56.1' W., between sections 8 and 17.

39.910

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E	
S 8	
1/4	_____
S 17	
2005	

Set a steel fence post alongside the stainless steel post.

79.820

The corner of sections 7, 8, 17 and 18.

N. 89° 44.7' W., between sections 7 and 18.

40.080

The 1/4 section corner of sections 7 and 18, monumented with an iron post, 1 inch diameter, projecting 12 inches above ground, with brass cap marked as described in the official record of the 1924 survey.

N. 89° 56.8' W., beginning new measurement.

22.320

The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. 34° 26.1' E. and S 34° 26.1' W.

39.572

The corner of sections 7, 12, 13 and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17 and 18.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 03.4'$ W., between sections 7 and 8.

20.028

Point for the S $1/16$ section corner of sections 7 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E
S $1/16$
S 7 | S 8
2005

Set a steel fence post alongside the stainless steel post.

39.568

The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, bears N. $65^{\circ} 30'$ E. and S. $65^{\circ} 30'$ W.

40.056

Point for the $1/4$ section corner of sections 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, with a brass cap marked:

T 43 S R 17 E
 $1/4$
S 7 | S 8
2005

60.084

Point for the N $1/16$ section corner of sections 7 and 8.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T 43 S R 17 E
N $1/16$
S 7 | S 8
2005

Set a steel fence post, 2 ft. ENE of the stainless steel post.

80.112

The corner of sections 5, 6, 7 and 8, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, with a magnet at base, in the center of the mound of stone, 6 inches to bedrock, 5 ft. base to top of brass cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 17 E

S 6	S 5
S 7	S 8

 2005

From the corner of sections 4, 5, 8 and 9.

N. 89° 57.1' W., between sections 5 and 8.

19.983 Point for the E 1/16 section corner of sections 5 and 8, not monumented.

39.966 The 1/4 section corner of sections 5 and 8, monumented with a mound of stone; there is no remaining evidence of the 1924 iron post.

At the corner point (center of the mound)

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
 S 5
 1/4 —————
 S 8
 2005

Raise a mound of stone, 3 ft. base, 2 ft. high, north of stainless steel post.

N. 89° 56.6' W., beginning new measurement.

39.883 The corner of sections 5, 6, 7 and 8.

N. 89° 54.2' W., between sections 6 and 7.

39.978 Point for the 1/4 section corner of sections 6 and 7, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
 S 6
 1/4 —————
 S 7
 2005

Set steel fence post alongside the stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located west, 20 links distance from a dirt road, bears NNE and SSW.

- 79.486 The corner of sections 1, 6, 7 and 12, on the west boundary of the township, hereinbefore described.

From the corner of sections 5, 6, 7 and 8.

N. 0° 00.6' E., between sections 5 and 6.

- 39.948 Point for the 1/4 section corner of sections 5 and 6, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
1/4
S 6 | S 5
2005

Set a steel fence post alongside the stainless steel post.

- 59.922 Point for the N 1/16 section corner of sections 5 and 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 3 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T 43 S R 17 E
N 1/16
S 6 | S 5
2005

- 79.896 The corner of sections 5, 6, 31 and 32, on the north boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 1,
T. 43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 1 and 12.

N. 0° 02.2' E., on the N - S centerline of section 1.

- 19.988 Point for the center S 1/16 section corner of section 1.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

THE SUBDIVISION OF SECTION 1,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 17 E
C
S 1/16 | S 1
C
2005

Set a steel fence post alongside the stainless steel post.

- 39.976** Point for the center 1/4 section corner of section 1, at intersection with the E-W centerline.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
C 1/4
S 1
2005

Set a steel fence post alongside the stainless steel post.

- 41.229** The centerline of a gravel road approximately 70 ft. wide, bears S. 56° E. and N. 56° W.
- 59.982** Point for the center N 1/16 section corner of section 1.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
C
N 1/16 | S 1
C
2005

Set a steel fence post alongside the stainless steel post.

Corner is located 1.700 chains east, of a wash, drains southeast.

- 79.988** The 1/4 section corner of sections 1 and 36, on the north boundary of the township, hereinbefore described.

From the corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 89° 56.4' W., on the E-W centerline of section 1.

- 38.202** Intersect the centerline of a gravel road, approximately 70 ft. wide, bears S. 51° E. and N. 51° W.
- 39.987** The center 1/4 section corner of section 1.
- 80.001** The 1/4 section corner of sections 1 and 2.

THE SUBDIVISION OF SECTION 1,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the N 1/16 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 89° 54.7' W., on the E-W center line of the NE 1/4 of section 1.

39.976 The center N 1/16 section corner of section 1.

From the S 1/16 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 89° 57.4' W., on the E-W centerline of the SE 1/4 of section 1.

15.000 The centerline of a gravel road approximately 70 ft. wide, bears S. 52° E. and N. 52° W.

39.997 The center S 1/16 section corner of section 1.

THE SUBDIVISION OF SECTION 5,
T. 43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 section corner of sections 5 and 8.

N. 0° 05.1' E., on the N-S centerline of section 5.

19.980 Point for the center S 1/16 section corner of section 5, not monumented.

39.960 Point for the center 1/4 section corner of section 5, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with brass cap marked:

T 43 S R 17 E
C 1/4
S 5
2005

Set a steel fence post alongside the stainless steel post.

59.939 Point for the center N 1/16 section corner of section 5.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 43 S R 17 E
C
N 1/16 | S 5
C
2005

Set a steel fence post alongside the stainless steel post.

79.918 The 1/4 section corner of sections 5 and 32, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 4 and 5.

N. 89° 57.7' W., on the E-W centerline of section 5.

19.987 Point for the center E 1/16 section corner of section 5.

Set s stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T 43 S R 17 E
E 1/16
C ——— C
S 5
2005

39.974 The center 1/4 section corner of section 5.

79.906 The 1/4 section corner of sections 5 and 6.

From the center E 1/16 section corner of section 5.

N. 0° 05.6' E., on the N-S centerline of the NE 1/4 of section 5.

19.981 Point for the NE 1/16 section corner of section 5, at intersection with the E-W centerline of the NE 1/4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
NE 1/16
S 5
2005

Set a steel fence post alongside the stainless steel post.

39.962 The E 1/16 section corner of sections 5 and 32 on the north boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the N 1/16 section corner of sections 4 and 5.

N. 89° 58.1' W., on the E-W centerline of the NE 1/4 of section 5.

19.989 The NE 1/16 section corner of section 5.

39.978 The center N 1/16 section corner of section 5.

From the point for the E 1/16 section corner of sections 5 and 8.

N. 0° 05.6' E., on the N-S centerline of the SE 1/4 of section 5.

19.982 Point for the SE 1/16 section corner of section 5, at intersection with the E-W centerline of the SE 1/4.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
SE 1/16
S 5
2005

Set a steel fence post alongside the stainless steel post.

39.964 The center E 1/16 section corner of section 5.

From the S 1/16 section corner of sections 4 and 5.

N. 89° 57.4' W., on the E-W centerline of the SE 1/4 of section 5.

19.985 The SE 1/16 section corner of section 5.

39.970 The point for the center S 1/16 section corner of section 5.

THE SUBDIVISION OF SECTION 6,
T. 43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 section corner of sections 6 and 7.

N. 0° 06.4' E., on the N-S centerline of section 6.

39.983 Point for the center 1/4 section corner of section 6, at intersection with the E-W centerline.

THE SUBDIVISION OF SECTION 6,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
C 1/4
S 6
2005

Set a steel fence post alongside the stainless steel post.

59.982

Point for the center N 1/16 section corner of section 6.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
C
N 1/16 | S 6
C
2005

Set a steel fence post alongside the stainless steel post.

79.981

The 1/4 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 5 and 6.

N. 89° 51.3' W., on the E-W centerline of section 6.

39.907

The center 1/4 section corner of section 6.

79.450

The 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

From the N 1/16 section corner of sections 5 and 6.

N. 89° 49.1' W., on the E-W centerline of the NE 1/4 of section 6.

39.871

The center N 1/16 section corner of section 6.

From the center N 1/16 section corner of section 6.

N. 89° 50.5' W., on the E-W centerline of the NW 1/4 of section 6.

THE SUBDIVISION OF SECTION 6,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.561 The N 1/16 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 7,
T. 43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

From the 1/4 section corner of sections 7 and 18.

N. 0° 00.6' E., on the N-S centerline of section 7.

- 19.983 Point for the center S 1/16 section corner of section 7, falls within the right-of-way of United States Highway No. 163

Set a "T" iron, 18 inches long, flush and on the southeast edge of a paved road.

From which

A stainless steel post, 30 inches long, 2 1/2 inches diameter, set 18 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top, for a reference monument, bears S. 88° 49.0' E., 1.836 chains distance, with brass cap marked: RM S7 2005, and an arrow pointing to the corner.

A United States Highway No. 163 right-of-way marker bears S. 10°31.0' E., 1.066 chains distance, marked: CL 75 STA 371 1521 ELV 551404 1971.

- 20.235 The centerline of United States Highway No. 163, a paved road with 150 feet between rights-of-way, on a curve that bears to N. 65° 30' E. and S. 34° 26.1' W.

- 39.966 Point for the center 1/4 section corner of section 7, at intersection with the E-W centerline.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T 43 S R 17 E
C 1/4
S 7
2005

Set a steel fence post alongside the stainless steel post.

- 59.984 Point for the center N 1/16 section corner of section 7.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at

THE SUBDIVISION OF SECTION 7,
TOWNSHIP 43 SOUTH, RANGE 17 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

base, in a mound of stone, 4 ft. base to top of brass cap
marked:

T 43 S R 17 E
C
N 1/16 | S 7
C
2005

Set a steel fence post 4 ft. northeast of stainless steel
post.

80.002 The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

N. 89° 52.4' W., on the E-W centerline of section 7.

40.029 The center 1/4 section corner of section 7.

79.569 The 1/4 section corner of sections 7 and 12, on the west
boundary of the township, hereinbefore described.

From the N 1/16 section corner of sections 7 and 8.

N. 89° 53.3' W., on the E-W centerline of the NE 1/4 of
section 7.

40.003 The center N 1/16 section corner of sections 7.

From the S 1/16 section corner of sections 7 and 8.

N. 89° 48.6' W., on the E-W centerline of the SE 1/4 of
section 7.

40.054 The center S 1/16 section corner of section 7.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

T.43 S., R. 17 E., SALT LAKE MERIDIAN, UTAH

FIELD ASSISTANTS

Name	Capacity
Glen B. Hatch	Cadastral Surveyor
Tyler Trujillo	Survey Technician
Brandon Sanchez	Survey Technician
Daniel W. Webb	Chief Cadastral Surveyor

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of **the 11th day of July, 2005**, I have executed a dependent resurvey of the **Utah-Arizona state boundary line from Mile Post 219 to Mile Post 226, the east, west and north boundaries, the subdivisional lines and the subdivision of sections 1, 5, 6 and 7, in Township 43 South, Range 17 East,**

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 3, 2006
Date

Ronald K. Baugh
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of the Utah-Arizona state boundary line from Mile Post 219 to Mile Post 226, the east, west and north boundaries, the subdivisional lines and the subdivision of sections 1, 5, 6 and 7, in Township 43 South, Range 17 East,**

executed by **Ronald K. Baugh, Cadastral Surveyor,**

having been critically examined and found correct, are hereby approved.

June 16, 2006

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah